

John Deere 6125 HF070	Newage Stamford HCI 444	Generator Model:	BCJD 440-50
--------------------------	----------------------------	---------------------	--------------------

50 Hz	3-Phase	Power Factor Cos $\Phi = 0.8$	TAL-4g
-------	---------	----------------------------------	--------

RATINGS	PRIME POWER (PRP)		STANDBY POWER (LTP)		
	kVA	kWe	kVA	kWe	Amps
Voltage					
440/254	400	320	440	352	577
415/240	400	320	440	352	612
400/230	400	320	440	352	635
380/220	400	320	440	352	669

Definition of Ratings & Reference Conditions

Prime Power (PRP) is the nominal output continuously available, where the average load (variable) does not exceed 70% of the prime power rating. 10% overload is available for a maximum of 1 hour in 12 hours of operation.

Standby Power (LTP) is the maximum output available, for up to 500 hours per year, where the average load (variable) does not exceed 70% of the standby power rating. No overload is available.

Standard Reference Conditions: air temperature 25°C (77°F), barometric pressure 99kPa, [110m(361ft) altitude], 30% relative humidity.


Note: The above ratings may be subject to derate at different operating conditions. Please see the Derate Guidelines on the Broadcrown Website.

All power ratings and reference conditions in accordance with ISO 8528-1 and ISO 3046-1.



Key Features:

- Water cooled John Deere Diesel engine with ECU/CANBus
- Single bearing Newage Stamford alternator
- Radiator with pressure cap and drain point
- Fully guarded engine-driven fan
- Fully welded steel skid base with fork lift pockets
- Integral fuel tank with filler cap and gauge
- Heavy duty rubber anti-vibration mountings
- 12V starter battery and connecting cables
- Separate engine-driven battery charging alternator
- Spin on oil and fuel filters and dry type air filter element
- Industrial silencer (15dBA reduction) supplied loose
- Auto Start control system with digital instrumentation
- Main line circuit breaker
- Factory Test Certificate
- Operation & Maintenance Manual
- Wide range of optional extra features available



Overall Dimensions & Weights - Open Set

Length (L) = 3360mm
Width (W) = 1150mm
Height (H) = 2110mm

Dry Weight (inc oil) = 3100kg
Operating Weight = 3700kg

Typical Open Generator Sound Pressure Level at 1m, Free Field (dB)								
Overall dBA	63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
103	91	93	95	98	99	96	92	87

All specifications and design are subject to change without notice

ENGINE & COOLING SYSTEM
JOHN DEERE 6125 HF070

		SI Units	PRIME	STANDBY
Performance	Engine Speed	r/min	1500	
	Gross Power	kWm	350	387
	Fan Power	kWm	15	15
	Net Power	kWm	335	372
	Emissions Certification		TAL-4g	
	Altitude Capability	m	2730	2700
General	Cylinders / Type		6 cyl / inline / 4-stroke / HPCR	
	Aspiration / Charge Cooling		Turbocharged / Air to Air	
	Governing / Engine Management		Electronic Governor / ECU / CANBus	
	Bore / Stroke	mm	127 / 165	
	Cubic Capacity	litres	12.5	
	BMEP	kPa	2233	2469
Fuel	Fuel Consumption at 100% Power	litres/h	81.0	87.5
	Fuel Consumption at 75% Power	litres/h	59.4	64.0
	Fuel Consumption at 50% Power	litres/h	40.4	42.9
	Total fuel flow	litres/h	147	
	Standard Fuel Tank Capacity	litres	650	
Air	Engine Air Flow	m³/s	0.430	0.447
	Maximum Air Intake Restriction (used filter)	kPa	6.25	
Exhaust	Exhaust Gas Flow	m³/s	1.018	1.080
	Exhaust Gas Temperature	°C	462	468
	Maximum Exhaust Back Pressure	kPa	7.5	
	Typical Exhaust Pipe Diameter	mm	200	
Cooling	Radiator Cooling Air Flow	m³/s	9.5	
	Max Restriction to Cooling Air Flow	Pa	250	
	Max Radiator Air-On Temperature	°C	50	
	Maximum Coolant Temperature	°C	105	
	Coolant Capacity - Engine Only	litres	16.2	
	Total Coolant Capacity	litres	20	
Oil	Total Oil Capacity incl Filters	litres	42	
	Typical Oil Pressure at Rated Speed	kPa	275	
	Typical Oil Consumption (>250hrs Operation)	litres/h	0.21	
Thermal	Heat Rejection to Engine Cooling Water	kW	137	140
	Heat Rejection to Charge Cooler	kW	65	77
	Heat Radiated From Engine (Typical)	kW	44	48
Elec	Electrical System Voltage	V	12	
	Battery Type		2 (Parallel) 656	
	Battery Capacity SAE CCA	A	1620	

ALTERNATOR
NEWAGE STAMFORD HCI 444

		SI Units	PRIME	STANDBY
General Data	Manufacturer		NEWAGE STAMFORD	
	Model (may vary with voltage)		HCI 444 F	HCI 444 F
	Operating Temperature	°C	40	27
	Coupling / No. of Bearings		Direct / Single Bearing	
	Phase / Poles / Winding Type		3-Phase / 4-Pole / Winding 311	
	Power Factor		Cos Φ = 0.8	
	Excitation		Self Excited	
	Insulation System		Class H	
	AVR Type		AS 440	
	Voltage Regulation		± 1.0%	

All specifications and design are subject to change without notice

STANDARD CONTROL SYSTEM

BC 5310 Digital Auto Start

The standard control system for this model is **BC 5310** (photo), based on the Deep Sea Electronics DSE5310 Digital Auto Start controller.

This provides for the manual and automatic remote start of the generator, together with full CANBus implementation for the control and protection of the engine via the ECU. LCD digital display of :

- Coolant temperature with high temperature alarm and shutdown
- Oil pressure with low pressure alarm and shutdown
- Oil temperature, engine operating hours, battery charge volts and amps
- Volts, with Under/Over Volts protection
- Amps, with Over Current protection
- Frequency, kW, kVA, Power Factor

Also featuring :

- Full RS485 Telemetry implementation
- Automatic cool-down timer function
- Emergency Stop button
- Ample auxillary inputs/outputs for optional features
- Optional (shown) - battery charger and door mounted illuminated switch.



The panel is constructed in 1.5mm steel, powder coated to RAL9001 for a high quality, durable finish.

CONTROL SYSTEM OPTIONS

The **BC 5320** control system (just the DSE5320 module is shown here) has an identical feature set to the BC 5310 but with the addition of full AMF functionality with integrated mains monitoring.



Finally, **BC 5510 & BC 5520** control systems provide the same features as BC 5310 & BC 5320 respectively, plus :

- BC 5510 - Set-to-Set Synchronisation
- BC 5520 - Single Set-to-Mains Supply Synchronisation with integrated mains monitoring

For Multi Set-to-Mains synchronisation, each set requires BC 5510 with the addition of one mains monitoring panel **BC 5560** (not illustrated). See the Synchronisation Guidelines for further details.

All specifications and design are subject to change without notice

OPTIONAL ACOUSTIC ENCLOSURE

Canopy 5

The optional acoustic enclosure for this model is **Canopy 5**, suitable for operation in harsh outdoor environments whilst providing excellent security and acoustic performance. The steel canopy is of fully welded construction with a two-pack polyurethane egg-shell finish in RAL9001 white. The baseframe is finished in RAL9005 satin finish black.

Acoustically, the canopy is designed to meet the requirements of EU Legislation 2000/14/EC, achieved by extensive use of rock wool and perforated zintec steel lining, together with efficient management of cooling air. Exhaust noise is minimised by a unique high performance exhaust silencer, mounted within the baseframe.

A steel fuel tank with filler, gauge and accessory points, is integrated within the baseframe. Alternatively, a bund with separate fuel tank can be provided where this is required.

Other key features include :

- Side-opening doors with retainers for good service access
- Control panel viewing window
- External service access panels
- Heavy duty locks on all doors for total security
- Weather cap on exhaust discharge
- Emergency Stop button relocated to canopy exterior
- Lifting and holding down points on baseframe
- Single roof lifting point.



Dimensions (mm)				Additional Weight (kg) *	Typical Sound Pressure Level at 75% of Prime Power		Fuel Tank Capacity (Litres)		Single Point Lift	
L	x	W	x		H	dB(A) at 1m	dB(A) at 7m	Integral		Bunded
5350	x	1600	x	2370	2400	77	67	900	800	Standard

* Indicative weight of canopy *additional* to open set

Typical SPL is a mean level, measured in free field conditions, with no contributory background noise.

KEY MECHANICAL OPTIONS (Open Set)

Engine & Cooling :

- Electronic governor
- Oil and coolants drains extended to edge of baseframe
- Manual lub oil drain pump
- Coolant heater
- Medium duty air cleaner
- Exhaust manifold guards

Alternator :

- Anti-condensation heater
- Quadrature droop kit
- Alternative AVR
- Thermistor probes and controls

Fuel System :

- Baseframe with integral bund and drop-in fuel tank
- Fuel filter/separator
- Low fuel level switch (single point)
- Fuel level switch (four point)
- Manual fuel transfer pump
- Pumped/gravity fuel transfer system

Exhaust System :

- Residential silencer
- Critical silencer
- Flange/connection kit

Please refer to Broadcrown Sales Department for full details of these and other options

All designs and specifications subject to change without notice