

GARDEN SPRAYER 1000 Lt - 600 Lt - 100 Lt



TECHNICAL SPECIFICATIONS OF POWER SPRAYERS

- Portable on 2 wheels.
- 5- 5,5 hp gasoline engine or monophasic electric motor.
- Tank capacity 100-200 ltr. Fiber-glass.
- 3 diaphragm pump. (model e-30, e-40)
- Pressure regulator.
- 1 spraying hose of 15 mts. Length.
- 1 spraying gun. Length and adjustable nozzles.

TECHNICAL SPECIFICATIONS OF GARDEN SPRAYERS

- These sprayers with 400, 500, 600 lt tank capacity are mounted to the tractor on three points linkage and operated through the p.t.o shaft of the tractor.
- There is also a trailer mounted version with 1000, 1600, 2000 lt tank capacity.
- Clean water tank (trailer models)
- Tank material is fiber-glass or polyethylene and protected against all pesticides.
- Self filling system.
- Pressure regulator.
- The filter can be cleaned any time.
- Hydraulic agitator.
- Two spray gun and two 15 mt pressure hose are standard accessories.
- Hose reel. (optional)
- Medium - pressure membrane pump or high - pressure membrane pump.
- Guarded cardan shaft.

Technical Specifications	Model			
	AGS 100	AGS 200	AGS 400	AGS 500
Capacity & Machine (Lt)	100	200	400	500
Total Width (mm)	850	860	880	900
Total Length (mm)	1800	1825	1150	1280
Total Height (mm)	840	840	1250	1320
Hose (m)	15	15	2x15	2x15
Spray Gun (pieces)	1	1	2	2
Pump*	E-40	E-40	E-55	E-55

Technical Specifications	Model			
	AGS 600	AGS 1000	AGS 1600	AGS 2000
Capacity & Machine (Lt)	600	1000	1600	2000
Total Width (mm)	900	1500	1500	1500
Total Length (mm)	1280	2350	2450	3350
Total Height (mm)	1400	1520	1600	1600
Hose (m)	2x15	2x15	2x15	2x15
Spray Gun (pieces)	2	2	2	2
Pump*	E-55	E-105	E-125	E-125

PUMP TABLE	Model					
	E-30	E-40	E-55	E-81	E-105	E-125
Diaphragm No	3	3	3	3	4	5
Delivery (Lt/Min)	30	40	55	81	105	125
Pressure (Bar)	40	40	40	50	50	50

PUMP TABLE	Model				
	E-151	E-125A	E-155A	E-121	E-145
Diaphragm No	6	4	4	3	4
Delivery (Lt/Min)	151	125	155	120	145
Pressure (Bar)	50	50	50	50	50